

# THUNDER TC4340X

Emergency phone in cab



## Features

- ADA, ASME A17.1-2019/CSA B44:19 compliant.
  - Self-diagnostic as required per code.
  - Upgradable remotely or with USB drive.
- Camera code compliant with entire floor view.
- Easy installation camera in COP: one cable for audio, microphone and video.
- External PoE port available as an option.
  - Dipswitch configurable.
    - Full-duplex VoIP.
    - 4.3" color LCD.



917 Mgr Grandin, Suite 304B  
Quebec City  
Quebec, Canada  
G1V 3X8  
1 418 476-4802  
info@vidatech.ca

TO ORDER :

TC4340X

Ethernet switch  
" " : None  
"S" : With switch

# TC4340 SPECIFICATIONS

TC4340	
Wiring	18/20 AWG Single Twisted Pair (Max 1000m) Canbus
Dimensions	Screen: 220 x 110 x 25.3mm Camera module: 220 x 80 x 27.2mm
Screen	TFT-IPS 4.3in diagonal 95 x 54mm screen area 800 x 480 pixels 65 536 colors
Power	24 - 57V, 6.5W
Flash Memory	64 MB
Compliance	ADA ASME A17.1-2019, CSA B44-19 ASME A17.1-F2019 CSA B44-F19
Speaker	8ohm 2W
Microphone	Omnidirectional electret condenser
Operating Temperature	0 - 45 °C
Weight	2 lb, 0.90Kg
Warranty	1 year from installation date
Protocol/Communication	SIP, RFC2833, RTP, NTP, STUN
Security	TLS1.3, Encrypted Firmware, AES256

# TC4340S SPECIFICATIONS

TC4340S	
Wiring	18/20 AWG Single Twisted Pair (Max 1000m) Canbus
Dimensions	Screen: 220 x 110 x 25.3mm Camera module: 220 x 80 x 27.2mm
Screen	TFT-IPS 4.3in diagonal 95 x 54mm screen area 800 x 480 pixels 65 536 colors
Power	24 - 57V, 6.5W
Flash Memory	64 MB
Compliance	ADA ASME A17.1-2019, CSA B44-19 ASME A17.1-F2019 CSA B44-F19
Speaker	8ohm 2W
Microphone	Omnidirectional electret condenser
Additional Interface	2 x Eth 1 x PoE Eth
Operating Temperature	0 - 45 °C
Weight	2 lb, 0.90Kg
Warranty	1 year from installation date
Protocol/Communication	SIP, RFC2833, RTP, NTP, STUN
Security	TLS1.3, Encrypted Firmware, AES256